


# Schottky Barrier Rectifiers

## PRODUCT SUMMARY


Surface Mount Low  $V_F$   
 Reverse Voltage 20 to 40 Volts  
 Forward Current 2.0 Amperes



## FEATURES

- For surface mounted application
- Metal silicon junction, majority carrier conduction
- Low forward voltage drop
- Easy pick and place
- High surge current capability
- Plastic material used carries Underwriters Laboratory Classification 94V-O
- Epitaxial construction
- High temperature soldering:  
 250°C / 10 seconds at terminals

DO-214AA (SMB)



Dimensions in inches and (millimeters)

## MECHANICAL DATA

Cases: Molded plastic  
 Terminals: Solder plated  
 Polarity: Indicated by cathode band  
 Weight: 0.003 ounce, 0.093 gram



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.






Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Parameter	Symbols	SL22	SL23	SL24	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	20	30	40	Volts
Maximum RMS voltage	$V_{RMS}$	14	21	28	Volts
Maximum DC blocking voltage	$V_{DC}$	20	30	40	Volts
Maximum average forward rectified current See Fig. 1	$I_{(AV)}$	2.0			Amps
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method )	$I_{FSM}$	50.0			Amps
Maximum instantaneous forward voltage @ 2.0A (Note 1)	$V_F$	0.385	0.385	0.400	Volts
Maximum DC reverse current at rated DC blocking voltage	$I_R$	3.0 150			mA
					@ $T_A=25^{\circ}C$ @ $T_A=100^{\circ}C$
Maximum thermal resistance (Note 2)	$R_{\theta JL}$ $R_{\theta JA}$	25 75			°C/W
Operating junction temperature range	$T_J$	-55 to +125			°C
Storage temperature range	$T_{STG}$	-55 to +150			°C

- Notes:**
1. Pulse Test with PW=300 usec, 1% Duty Cycle.
  2. Measured on P.C. Board with 0.2 x 0.2" (5.0 x 5.0 mm) Copper Pad Areas.

## RATINGS AND CHARACTERISTIC CURVES



Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, expressed or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.